

## SOLAR COLLECTORS

### SUPERLINE M-1 FSB SOLAR COLLECTOR

Superline M-1 FSB collectors are manufactured under high quality conditions. Contains sputtered blue high selective copper full-plate absorber surface, to get the best performance under poor solar radiation.

#### Technical information

Absorber: High selective coated full-plate copper sheet.

Front cover: Tempered low-iron solar glass with high transmittance

Frame: Electrostatic powder coated aluminium extrusion profiles

Insulation: Rockwool



#### Specifications

Type	Superline M-1 FSB	
Specification	Unit	Values
Dimensions (lengthxwidthxheight)	mm	1727x1204x99
Gross area	m <sup>2</sup>	2,08
Aperture area	m <sup>2</sup>	1,85
Cover thickness	mm	4
Cover material		tempered low-iron solar glass
Riser tubes material		copper
Riser tubes diameter	mm	Ø 8
Number of riser tubes	pcs.	10
Manifold tubes material		copper
Manifold tubes diameter	mm	Ø 22
Absorber type		grid (parallel) full-plate absorber
Absorber surface material		blue selective coated copper
Absorbance of absorber surface		0,95±0,02
Emittance of absorber surface		0,05±0,02
Empty weight of collector	kg	36
Frame material		electrostatic powder coated aluminium
Insulation material		rock wool
Insulation thickness lateral/rear	mm	25/40
Fluid volume of absorber	lt	1,42
Allowed heat transfer fluid		glycol
Maximum working pressure	bar	9
Sealing material		EPDM

#### EZINC METAL SAN. TIC. A.S.

O.S.B. 23. Cadde No:31 TR-38070 Kayseri - TURKEY

Tel: +90 352 3211321 - Fax: +90 352 321325

sales@ezinc.com.tr

www.ezinc.com.tr